



**ALT 708**

**THE NEW  
TELESCOPIC  
ARTICULATED  
LOADER**



# THE NEW TELESCOPIC ARTIC

## ● COMFORT and ● PERFORMANCE

### ● COMFORT

#### High visibility

- Cab in a central position
- Roof window

#### Well-being inside the cab

- Joystick on floating armrest
- Telescopic tilting steering column
- Right side and rear opening windows
- Optional air suspension seat
- Bluetooth hands-free radio in option

### ● PERFORMANCE

- High flow option
- Hydraglide boom suspension as an option
- Proportional auxiliary hydraulics with pressure free return and circuit pressure release
- Speed control as an option
- 30 km/h top speed as an option

### ● APPLICATIONS

- Feed animals
- Handle straw and hay bale
- Handle big bags
- Load feeder wagons
- Load manure in animal housing
- Load compost

### ● TO EACH ITS OWN STYLE

- 3 operator stations: canopy, canopy with front/rear glass, full cab
- Different attachment carriages available
- Complete range of attachments

- 1 High performance capacity
  - Static tipping load bucket
  - Static tipping load bucket
- 2 Power-A-Tach<sup>®</sup> attachment equipment



# CULATED LOADER

ALT 708

capacities:

bucket retracted 3012 kg/3535 kg

bucket extended 1727 kg/1846 kg

mounting system standard

**3** Reversing fan

**4** Auxiliary Hydraulic Options for Owner/Operator preference

**5** Road, Work and Boom lights (LED optional)

**6** Telescopic lift arm with Z-bar bucket linkage, float detent, cushioned cylinders and mechanical self-leveling

**7** Multi-function joystick

Proportional auxiliary hydraulics, F-N-R, 4-wheel differential lock, 2-3 speed in option

**8** Canopy and cab options available

**9** Inching pedal, travel pedal and hand throttle

**10** Tire options for excellent ground engaging performance



# T708

## TELESCOPIC ARTICULATED LOADER

# NEW



### SPECIFICATIONS

	T708	
DIMENSIONS	Height to Top of Cab / ROPS	2476 mm
	Width over Tires	1957 mm
	Length with Bucket on Ground	5730 mm
	Shipping Length - No Bucket	4927 mm
	Bucket Hinge Pin Height Retracted	3911 mm
	Bucket Hinge Pin Height Extended	5036 mm
	Maximum Dump Angle at Full Height	45°
	Outer Turning Radius	4030 mm
Articulation Angle from Center	40°	
CAPACITIES	Static Tipping Load with Bucket Retracted	3535 kg
	Static Tipping Load with Bucket Extended	1846 kg
	Bucket Breakout	4990 kg
	Operating Weight with Bucket	5543 kg
ENGINE	Engine Manufacturer	Deutz
	Model / Number of Cylinders	TD 3.6 L / 4
	Gross Power @ 2300 rpm	55 kW
	Displacement (L)	3.6 L
HYDRAULICS	Work Hydraulic System Flow	70 L/min
	Drive Hydraulic System Pressure	380 bar
	Drive Hydraulic Reservoir Capacity	73.7 L
OTHER	Travel Speeds	8/20 km/h
	Battery	12 V
	Fuel Tank Capacity (L)	115 L
	Tires	405 / 70 20

### TIRE OPTIONS

HIGH  
FLOTATION



Ag / Industrial Tires

NON-DIRECTIONAL  
SELF-CLEANING



On / Off Road / Industrial Tires

AG/INDUSTRIAL  
HYBRID UNIVERSAL



On / Off Road Tires

#### SPECIFICATIONS ARE PRELIMINARY

Mustang reserves the right to add improvements or make changes in features and specifications at any time without notice or obligation.

Mustang reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.

Mustang reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.

Mustang reserves the right to add improvements or make changes in features and specifications at any time without notice or obligation.

**MUSTANG**  
eu.mustangmfg.com

MANITOU GROUP

430 rue d'Aubinière - F- 44150 - ANCENIS, Tel: +33 240091011